

HyPrint 1200

Naphthenic Ink Oil Marketing Specification

This severely hydrotreated naphthenic printing ink oil has a low odor level, and good solvency and volatility.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL VALUES
		MIN	MAX	
Physical Properties				
Viscosity, SUS at 100°F (37.8°C)	ASTM D2161	1200	1300	1244
Viscosity, SUS at 210°F (98.9°C)	ASTM D2161			77.4
Viscosity, cSt at 40°C (104°F)	ASTM D445	220	240	230
Viscosity, cSt at 100°C (212°F)	ASTM D445			14.4
API Gravity, 60°F (15.6°C)	ASTM D1250			22.1
Specific Gravity, 60°F (15.6°C)	ASTM D4052			0.9215
Viscosity-Gravity Constant	ASTM D2501			0.853
Density, lbs/gal at 60°F	ASTM D1250			7.675
Density at 15.6°C, g/cm ³	ASTM D1250			0.9206
Molecular Weight	ASTM D2502			456
Flash Point, COC, °F (°C)	ASTM D92	410 (210)		466 (241)
Flash Point, PMCC, °F (°C)	ASTM D93	383 (195)		432 (222)
Color, ASTM	ASTM D6045		3.0	L2.0
Pour Point, °F (°C)	ASTM D5949		25 (-4)	-17 (-27)
Water Content	ASTM D7546M	PASS		PASS
Appearance	ASTM D4176M	PASS		PASS
Chemical Properties				
Aniline Point, °F (°C)	ASTM D611	195 (91)	210 (99)	202 (94)
Health and Safety Properties				
Polycyclic Aromatic Compounds, wt%	IP 346		3	<3
Modified Ames Assay, MI	ASTM E1687		1	<1

HyPrint 1200 is a product of Ergon Refining, Inc.
March 2, 2020