

HyPrint MVI 150BS

Naphthenic Ink Oil Marketing Specification

This severely hydrotreated naphthenic printing ink oil has a low odor level, and good solvency and volatility.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL VALUES
		MIN	MAX	
Physical Properties				
Viscosity, SUS at 100°F (37.8°C)	ASTM D2161			3722
Viscosity, SUS at 210°F (98.9°C)	ASTM D2161	130	180	161
Viscosity, cSt at 40°C (104°F)	ASTM D445			680
Viscosity, cSt at 100°C (212°F)	ASTM D445	26.0	37.0	32.8
API Gravity, 60°F (15.6°C)	ASTM D1250			23.2
Specific Gravity, 60°F (15.6°C)	ASTM D4052			0.9144
Viscosity-Gravity Constant	ASTM D2501			0.827
Density, lbs/gal at 60°F	ASTM D1250			7.615
Density at 15.6°C, g/cm ³	ASTM D1250			0.9135
Molecular Weight	ASTM D2502			625
Flash Point, COC, °F (°C)	ASTM D92	500 (260)		516 (269)
Flash Point, PMCC, °F (°C)	ASTM D93	410 (210)		469 (243)
Color, ASTM	ASTM D6045		4.0	L2.5
Pour Point, °F (°C)	ASTM D5950		45 (7)	36 (2)
Water Content	ASTM D7546M			PASS
Appearance	ASTM D4176M	PASS		PASS
Chemical Properties				
Aniline Point, °F (°C)	ASTM D611	220 (104)	258 (125)	243 (117)
Health and Safety Properties				
Polycyclic Aromatic Compounds, wt%	IP 346		3	<3
Modified Ames Assay, MI	ASTM E1687		1	<1

HyPrint MVI 150BS is a product of Ergon Refining, Inc.
February 9, 2024