

HyPrene L2000

Naphthenic Process Oil Marketing Specification

This severely hydrotreated naphthenic process oil provides good solvency for the rubber and chemical processing industries. It has a low pour point, a low odor level, excellent color, and resistance to discoloration by heat or ultraviolet light.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL VALUES
		MIN	MAX	
Physical Properties				
Viscosity, SUS at 100°F (37.8°C)	ASTM D2161	2000	2400	2139
Viscosity, SUS at 210°F (98.9°C)	ASTM D2161			100.2
Viscosity, cSt at 40°C (104°F)	ASTM D445	367	435	390
Viscosity, cSt at 100°C (212°F)	ASTM D445	19.0	25.0	19.7
API Gravity, 60°F (15.6°C)	ASTM D1250			21.6
Specific Gravity, 60°F (15.6°C)	ASTM D4052			0.9244
Viscosity-Gravity Constant	ASTM D2501			0.849
Density, lbs/gal at 60°F	ASTM D1250			7.699
Density at 15.6°C, g/cm ³	ASTM D1250			0.9235
Molecular Weight	ASTM D2502			500
Flash Point, COC, °F (°C)	ASTM D92	470 (243)		508 (264)
Flash Point, PMCC, °F (°C)	ASTM D93	437 (225)		457 (236)
Color, ASTM	ASTM D6045		4.0	L2.0
Pour Point, °F (°C)	ASTM D5949		30 (-1)	-8 (-22)
Volatility, wt%, 225°F (Evap. Loss)	ASTM D972			0.16
Water Content	ASTM D7546M		PASS	PASS
Appearance	ASTM D4176M		PASS	PASS
Glass Transition Temperature (Tg), °C	ASTM D3418			-55
Chemical Properties				
Acid Number, mg KOH/g	ASTM D664		0.05	0.01
Aniline Point, °F (°C)	ASTM D611	200 (93)	215 (102)	209 (98)
Sulfur, ppm	ASTM D4294			795
Refractive Index, 20°C (68°F)	ASTM D1218			1.5075
UV Absorptivity at 260 nm	ASTM D2008			4.23
Clay-Gel, wt%	ASTM D2007			
Asphaltenes				<0.1
Polar Compounds				2.1
Aromatics				42.0
Saturates				56.0
Carbon Type Analysis, %	ASTM D2140			
Ca				12
Cn				35
Cp				53
Health and Safety Properties				
Polycyclic Aromatic Compounds, wt%	IP 346		3	<3
Modified Ames Assay, MI	ASTM E1687		1	<1